



CERTIFICATE OF ENGINEERING ACCEPTANCE

This certificate is issued in accordance with RIS-1530-PLT Issue 5

NAME OF VEHICLE ACCEPTANCE BODY

SNC-Lavalin Rail & Transit Limited

ACCREDITATION CODE

IF

Vehicle Class / Description

919/Rexquote/Demag AC40 Crane/9A

Vehicle Owner

Road Rail Cranes Ltd

Issue Date

17 March, 2016

Expiry Date

16 August, 2020

Vehicle Number(s)

99709_919080-0

First Of Class

99709 919080-0 on certificate IF/0790/13 against RIS-1530-PLT, Issue 4

Authorised by:

Adrian Staples

SNC-Lavalin Rail & Transit Limited

astaples

OFFICIAL STAMP



SNC-LAVALIN

Reason for issue and Scope of Work

Update to EAC for Road Rail Demag AC40 Crane.
Demag Serial No. 70368. Rexquote Serial No. 2302.
On this EAC: Amendment to Limitation 11. Clarifying on/off tracking cant only. No engineering change.
Assessed for compliance with RIS-1530-PLT, Issue 5.
Expiry date conforms to the requirements of RIS-1530-PLT, Issue 5.

Deviations associated with this certificate

None

Previous Certificate Number

Previous Engineering Acceptance Certificate : IF0534/15.

Maintenance Plan Details

Rexquote Demag AC40 Crane, Rail Mounted Crane Operating and Maintenance Manual, RQM50106v03, Issue 2, 17/03/16.

Customer Copy

Certificate Number: IF/0148/16

Limitations of Use

1. When travelling, the vehicle is within W6a gauge as defined in RIS-1530-PLT.
2. Vehicle has NO WORKING MODE whilst on rail.
3. Vehicle shall not on/off track or travel on live conductor-rail lines.
4. Vehicle shall not on/off track if the adjacent line or lines are open to traffic, UNLESS otherwise permitted by a site-specific and Network Rail approved Adjacent Line Open (ALO) safe system of work plan.
5. Vehicle will not activate train operated points.
6. Vehicle shall not travel on track with:
 - > Cants greater than 200mm; gradients greater than 1:25; and/or curves less than 80m.
7. When reversing, the vehicle shall only proceed at walking speed with the driver utilising the CCTV and/or ground staff.
8. For access/egress, the vehicle shall only operate with the door to the cab adjacent to a cess or a line closed to all train movements, or the safe system of work takes account of adequate clearances to adjacent lines.
9. Setting up and packing away - from inside cab.
10. The upper-structure and stabilisers shall be stowed correctly before travelling on-rail.
11. Vehicle shall not be on/off tracked on cants greater than 165mm and/or gradients greater than 1:25.
12. For on/off tracking, a site specific work plan shall be used taking account of the applicable Module in Network Rail Infrastructure Plant Manual NR/PLANT/0200 and Rexquote manual RQM50106v03.
13. Vehicle shall not on/off track or travel under live OLE, except :-
 - > It may on/off track on an approved RRAP or travel under live OLE, when used in conjunction with a safe system of work determined and authorised by taking guidance from the requirements of GE/RT8024, and provided the upper-structure is in the travel position, taking account of the height of the top of the crane 3.365m above rail and subject to a minimum OLE wire height of 4.165m.
 - > Other than for the cab, access is NOT permitted onto any surfaces higher than 1.4m above rail when the vehicle is under live OLE.
14. It is permitted to tow and/or propel trailers with compatible coupling and air park/service brake systems. Air supply pressure for park brake release is 8bar, and for service brake is 0-8bar. Maximum weight is 40tonnes / 3 trailers fitted with air reservoirs.

NOTE: The maximum towed and/or propelled weight may have to be reduced where the railhead conditions for adhesion and/or running gradient may affect the safe traction performance of the vehicle.

Supplementary Information

1. The vehicle is a Rexquote rail conversion of a Demag AC40-1 City Crane.
2. Manufacturer Serial No. 70368. Rexquote Serial No. 2302.
3. The vehicle shall only operate on rail in high-mode.
4. Fitted with Rexquote direct rail-wheel braking.
5. The vehicle is approved to carry 1 person seated in the drivers cab.
6. CCTV camera fitted to the side and rear.
7. Gross vehicle weight: 36tonnes.
8. Maximum speeds travelling on rail not to exceed:-
 - 20mph plain line;
 - 5mph switches and crossings;
 - 5mph raised check/guard rails;
 - 10mph towing/propelling;
 - 5mph emergency recovery, refer also to the Rexquote manual RQM50106v03.

Note that Interfleet Technology Ltd is now trading as SNC-Lavalin Rail & Transit Ltd. This certificate has been issued on the basis of the Engineering Acceptance of Rail Vehicles Licence Agreement issued to Interfleet Technology Ltd (certificate numbers 13/017/001 and 13/017/002) on 1 February 2013, and subsequently extended until the termination of the CCB/VAB licensing process. The certification management system is unaffected by the change of name in respect of compliance with PS305/04