



## CERTIFICATE OF ENGINEERING ACCEPTANCE

This certificate is issued in accordance with RIS-1530-PLT Issue 4

NAME OF VEHICLE ACCEPTANCE BODY

*Interfleet Technology Ltd*

ACCREDITATION CODE

IF

Vehicle Class / Description

010/Chieftain/5mAA/0A

Vehicle Owner

Road Rail Cranes Ltd

Issue Date

21 May, 2014

Expiry Date

18 October, 2020

Vehicle Number(s)

99709\_010729-8

First Of Class

99709 010722-5 on Engineering Acceptance Certificate IF/0855/13 against RIS-1530-PLT, Issue 4.

Authorised by:

Bryan Lowe

*Interfleet Technology Ltd*

OFFICIAL STAMP

Reason for issue and Scope of Work

Certification of Chieftain 5m Rail Trailer.

Network Rail ID  
99709 010729-8

Serial No.  
RT 1149

Road Rail Cranes Fleet No.  
RRC 01

Originally assessed for compliance with RIS-1530-PLT, Issue 4.

On this certificate:  
Change to Maintenance plan reference.

Expiry date conforms the requirements of RIS-1530-PLT, Issue 4.

Deviations associated with this certificate

None

Customer Copy

Certificate Number: IF/0298/14



**Previous Certificate Number**

IF/0963/13 : 99709\_010729-8

**Maintenance Plan Details**

Chieftain Rail Operating and Maintenance Instruction Manual RM-09, Issue 4, 21/11/2013.

**Limitations of Use**

1. Trailer shall only be operated inside possessions
2. In travelling and working modes, the trailer is within W6a gauge, as defined by RIS-1530-PLT.
3. Trailer shall not on/off track or work on live conductor rails.
4. Trailer may on/off track, travel and work under live OLE in conjunction with a safe system of work as determined and authorised taking guidance from the requirements of GE/RT8024.
5. Trailer may not activate train operated points.
6. Trailer shall not travel or work on:
  - Track cants greater than 200mm;
  - Track gradients greater than 1:25;
  - Curves less than 80m.
7. Trailer cannot be on/off tracked in laden condition.
8. For on/off tracking, a site specific plan shall be used taking account of the applicable Module of Network Rail Infrastructure Plant Manual NR/PLANT/0200.
9. In travelling and working mode the trailer shall be subject to the limitations of the towing vehicle.
10. Trailer payload of 16,900 kg shall not be exceeded.
11. Trailer shall only be coupled to RRV's which are certified for towing or propelling this type of trailer.

**Supplementary Information**

1. Chieftain 4-wheel rail trailer with 5m bed to work with compatible RRV.
2. Serial No. RT 1149 Fleet No. RRC 01
3. Fitted with air spring-operated emergency/park brakes and air operated service brakes.
4. Air parking brake release pressure 5.6 - 8 bar; service brake pressure 0 - 8 bar.
5. Gross weight: 20,000 kg.
6. Maximum payload: 16,900 kg.
7. Tare weight: 3,100 kg.
8. Maximum speeds (travel and working) not to be exceeded:
  - 10mph plain line
  - 5mph switches and crossings
  - 1mph raised check/guard rails.